



ProCuity bed series

Safe.Smart.Scalable

ProCuity features advanced fall prevention, wireless technology and scalability. ProCuity is ergonomically designed for patient handling featuring Zoom Motorized Drive and electric breaks. ProCuity also offers a proactive approach to help prevent falls, reduce injury from falls, and streamline caregiver workflow. It's also scalable – accommodating clinical needs from Med/Surg units up to the ICU, helping hospitals standardise their bed fleet and improve caregiver efficiencies.



L model

29.2 cm low height
4" screen



LE model

29.2 cm low height
Electric brakes
USB outlet



Z model

35.6 cm low height
Zoom Motorized Drive

Specifications

ProCuity Specifications

Model number	3009
Overall length	
228.6 cm (without bed extender)	
259.1 cm (with bed extender)	
Width (siderails up)	
106,7 cm (42 in)	
Width (siderails down)	
106,7 cm (42 in)	
Height range (to litter top) L and LE models	
High: 76.2 cm (30 in)	
Low: 29.2 cm (11.5 in)	
Height range (to litter top) Zoom versions	
High: 81.3 cm (32 in)	
Low: 35.6 cm (14 in)	
Litter positioning	
Backrest: 0° to 65° ±5°	
Knee gatch: 0° to 30° ±5°	
Trend./Reverse Trend.: +12° to -12° ±5°	
Patient Surface	
213.4 cm x 88.9 cm (84 in x 35 in)	
Patient Surface with bed extender accessory:	
243.8 cm x 88.9 cm (96 in x 35 in)	
Caster Diameter:	
15.2 cm (6 in)	
Safe working load:	
249.5 kg (550 lb)	
Maximum patient weight:	
226.8 kg (500 lb)	

Standard features

- Bed scale*
- 3-zone Adaptive Bed Alarm
- iBed Watch
- Auxiliary outlets 230 VAC, 50 Hz, 8A
- Battery back-up
- Integrated bed extender
- Nurse call interface
- Pendant port
- Manual brakes
- Patient belongings holder
- Wireless capability
- Motion interrupt
- Integrated Foley hook
- Integrated restraint hooks
- Automatic under-bed light
- Integrated Pump holder
- 3-position siderails
- Smart Prompts and Safety Dashboard

Electronic specs

- Agency approvals: UL approved to IEC 60601
- Volts: 100-240 VAC
- Ampere rating: 8A
- Current leakage: Not more than 300 µA (microamps)
- Frequency: 50/60 Hz
- Hospital grade plug: 120 VAC, 60 Hz, 8A

*± 1.4 kg (3 lb) of total patient weight for patients who weigh 27.2 kg (60 lb) to (45.4 kg) (100 lb)

This document is intended solely for the use of healthcare professionals.

A healthcare professional must always rely on his or her own professional clinical judgment when deciding whether to use a particular product when treating a particular patient. Stryker does not dispense medical advice and recommends that healthcare professionals be trained in the use of any particular product before using it.

The information presented is intended to demonstrate the breadth of Stryker product offerings. A healthcare professional must always refer to the package insert, product label and/or instructions for use before using any Stryker product.

Products may not be available in all markets because product availability is subject to the regulatory and/or medical practices in individual markets. Please contact your Stryker representative if you have questions about the availability of Stryker products in your area.

Stryker Corporation or its divisions or other corporate affiliated entities own, use or have applied for the following trademarks or service marks: Stryker, iBed, Zoom, Secure Connect, ProCuity. All other trademarks are trademarks of their respective owners or holders. ProCuity : Class Im (2797).

The products depicted are CE marked in accordance with applicable EU Regulations and Directives.



OTHMED-OTH-121-27211-EN

OTHMED-OTH-121_27211-EN
RWS 08/2021
2020-27211

Copyright © 2021 Stryker
stryker.com